

CHARACTERISTICS

The EGG1U pyrocartridges were designed, tested and manufactured as a part of the ILR-33 AMBER 2K rocket project.

The need for having repeatable, available within short lead time, reliable and easily adjustable to wide pressure ranges were the reasons for the in-house development.

DESIGN

The body of the pyrocartridges is a metal casing with an external thread M12x1. Inside there is an electric fusehead with a no-fire current of 1 A and a main charge. The EGG1U pyrocartridges act as gas generators pyrotechnic devices whose initiation produces a hot gas at a given pressure within a given time. The resulting products of combustion can be used to perform work such as: opening/closing a valve, movement of a piston in an actuator, release of a mechanism lock, in parachute release systems, movement of a pyrotechnic cutter knife and many others.



TECHNICAL INFORMATION



Parameter	Value
Operating temperature range	-40 °C ÷ + 85 °C
No-fire current	≤1A/5 min
All-fire current	≥5 A / 50 ms
Thread	Ml2x1
Overall length	34 to 44 mm (depending on required pressure)
Mass	approx. 20 g
Range of pressures that can be generated	3 ÷ 12 MPa in the case of a (10 cm³ chamber)

BENEFITS

- The possibility of pressure adjustment without the need to interfere with the structure of the pyrocartridge.
- Flexibility of the technology application in many industries space, armament or aerospace.
- Price-competitive.
- Lack of primary explosives making it easier to transport as part of the transport of hazardous materials (ADR).
- Manufacturing in Poland (EU).





The Łukasiewicz Research Network - Institute of Aviation

offers a wide range of specialized research, engineering services and products. We provide comprehensive solutions, ranging from dedicated analyzes, simulations, engineering design, through the selection, testing and certification of materials and structures, to rapid prototyping and additive manufacturing.